

HDMI 8:8 & 6:6

Multiplexers

Model name: OHM 88 & OHM 66



<Front Panel of OHM 88>



<Front Panel of OHM 66>

Description

The products, OHM 88 and 66 enable you to switch up to 8 or 6 HDMI/DVI sources from HD set-top boxes or host computers in far locations to 8 or 6 digital HDTVs or displays by using not only general PC software like Hyperlink terminal (serial communication) or web browsers (LAN) but also Opticis' dedicated software in our shipping group. Easy programming feature for EDID setting and switching is accomplished in various manners such as manual input of front-panel key button or PC programming with various interfaces of RS-232, USB, and Ethernet.

The products have been designed not only to fully execute the DDC/HDCP function between any input and output switched, but also to have users designate any EDID to inputs for wide compatibility.

The products support wide-range compatibility with respect to systems, consisting of various HDMI/DVI graphic sources and HDTVs or DVI monitors. They also cover user's own programming with basic command sets of ASCII or Binary codes to offer flexible application with other video controllers or control software.

Features

- Enables to cross switch between one of 8 or 6 HDMI or DVI inputs and any of 8 or 6 HDMI or DVI outputs.
- Supports graphic computer resolution up to 1920x1200 at 60Hz and HD 1080p (1920x1080).
- Offers various user interface using WEB, USB, RS-232, LAN (TCP/IP) control and Front keys.
 - 1) WEB – Control by web browser like Internet Explorer.
 - 2) USB – USB 2.0 device compatible.
 - 3) RS-232 – various baud rates.
 - 4) LAN – TCP/IP communication.
 - 5) Front Keys – illuminated LED and toggle switch.
- Supports two options to set EDID for graphic source.
 - 1) Factory setting – EDID to each input in factory-out and able to restore it any time after taking other options.

- 2) EDID learning – able to read EDID from any of connected displays and store it to any of input ports.
- Offers three programming features for setting input and output connection and EDID setting as follows;
 - 1) Front keys – set an EDID to each input and execute switching.
 - 2) Opticis' dedicated PC program in the shipping group – install in your PC and set interface types and switching configuration.
 - 3) Hyperlink terminal in RS-232 interface and web browser in LAN interface.
- Supports not only DDC but also HDCP.
- Fulfill real-time display of in-out set-up status on LCD front window in tapping front keys.
- 19" Rack-mountable – Robust & Heavy duty casing.

Technical Information

- Signal type: Digital TMDS and Digital RGB.
- Fully supports HDCP function for digital content protection.
- Maximum Bandwidth: Single Link 1.65Gbps.
- Display resolutions: 480i to 1080p / 640 x 480 to 1600 x 1200 at 60Hz.
- Inputs: 8 or 6 HDMI Female ports / Output: 8 or 4 HDMI Female ports.
- Control or interface method: Front key, USB, RS-232, and LAN port.
- Power supply: AC-to-DC power adaptor – 110-240V 50/60Hz for AC and 12V, 5A for DC.
- Power consumption: 18 Watts for 8x8, 16 Watts for 6x6.
- Dimensions (W X D X H): 444mm X 230mm X 74mm for 8x8, 6x6, and 4x4.
- Weight: 6.2 Kg (13.66 lbs) for 8x8, 6.0 Kg (13.20lbs) for 6x6.
- Operating temperature & Humidity: 0~40℃, less than 80% humidity.

Ordering Information

OHM XX

Where x = 8: HDMI 8x8 multiplexer

6: HDMI 6x6 multiplexer

Shipping group: A - B USB cable, D-sub 9pin RS-232 cable, a firmware upgrade cable, CD (PC program), an AC/DC power adaptor and a user manual.

Headquarter

Opticis Co., Ltd.

907, ByusanTechnopia, 434-6
Sangdaewon-Dong, Chungwon-Ku,
Sunghnam City, Kyungki-Do, 463-
120
South Korea
Tel: +82 (31) 737-8033~9
Fax: +82 (31) 707-8079
www.opticis.com

North American Office

Opticis USA LLC

649 Route 206
Unit 9 Suite 307
Hillsborough, NJ 08844
Tel: 908-837-9652
Fax: 908-837-9078
cdkim@opticis.com